



Pacific NW Offshore

 Ilwaco, WA to Port Angeles, WA • 45th Annual Yacht Race

 June 10-13, 2021

Safety Equipment Requirements - 2/1/21

Source: This SER is based upon US Sailing SER revision 2020.

Inspection Procedure

- After you register an inspector will be assigned to you by CYC. (The current local Portland inspectors are Jeff Duvall, Thomas Keffer, Mary Hartel and Craig Garrison with others in Puget Sound to follow.)
- The Inspector will then call the skipper or point of contact and review any questions regarding SER compliance.
- After the review, fill out the inspection form/checklist and submit it to your Inspector.
- The Inspector will review it and will call back with any questions or additional information required.
- If an onboard inspection is required, your Inspector will coordinate with you on schedule and process.
- Inspectors and skippers should make every effort to finish onboard inspections prior to boat delivery to Ilwaco.
- Final, signed SERs shall be submitted to the race committee no later than 0800 hours (PDT), Thursday, June 10, 2021 per NOR 4.2.

Vessel Name

Skipper/Owner

Section Name **#** **Requirement** **Vessel Compliance**

Note Yes No

Overall	1.1	The Safety Equipment Requirements establish uniform minimum equipment and training standards for a variety of boats racing in differing conditions. These regulations do not replace, but rather supplement, the requirements of applicable local or national authority for boating, the Racing Rules of Sailing, the rules of Class Associations and any applicable rating rules.			
Overall: Responsibility	1.2	The safety of a boat and its crew is the sole and inescapable responsibility of the "person in charge", as per RRS 4, who shall ensure that the boat is seaworthy and manned by an experienced crew with sufficient ability and experience to face bad weather. S/he shall be satisfied as to the soundness of hull, spars, rigging, sails and all gear. S/he shall ensure that all safety equipment is at all times properly maintained and safely stowed and that the crew knows where it is kept and how it is to be used.			
Overall: Inspections	1.3	A boat may be inspected at any time by an equipment inspector or measurer appointed for the event. If it does not comply with these regulations, its entry may be rejected or it will be subject to a protest filed by the RC. A Violation of the Safety Equipment Requirements may result in a penalty other than disqualification.			
Overall: Equipment and Knowledge	1.4	All equipment required shall function properly, be regularly checked, cleaned and serviced, and be of a type, size and capacity suitable for the intended use and size of the boat and the size of the crew. This equipment shall be readily accessible while underway and, when not in use, stored in such a way that deterioration is minimized.			
Overall: Secure Storage	1.5	A boat's heavy items such as batteries, stoves, toolboxes, anchors, chain and internal ballast shall be secured.			
Overall: Strength of Build	1.6	A boat shall be strongly built, watertight and, particularly with regard to hulls, decks and cabin trunks, capable of withstanding solid water and knockdowns. A boat shall be properly rigged and ballasted, be fully seaworthy and shall meet the standards set forth herein. A boat's shrouds and at least one forestay shall remain attached at all times.			
Overall: Watertight Integrity	1.7	A boat's hull, including, deck, coach roof, windows, hatches and all other parts, shall form an integral watertight unit, and any openings in it shall be capable of being immediately secured to maintain this integrity.			
Hull and Structure: Hull Openings	2.1.1	A boat's companionway(s) shall be capable of being blocked off to main deck level (sheerline). The method of blocking should be solid, watertight, and rigidly secured, if not permanent.			
Hull and Structure: Hull Openings	2.1.2	A boat's hatch boards, whether or not in position in the hatchway, shall be secured in a way that prevents their being lost overboard.			
Hull and Structure: Cockpit	2.1.3	A boat's entire cockpit shall be solid, watertight, strongly fastened and/or sealed. Weather-tight seat hatches are acceptable only if capable of being secured when closed.			
Hull and Structure: Cockpit	2.1.4	A boat's cockpit drains shall be capable of draining six inches of water in 5 minutes. One square inch (645mm ²) of effective drain per eight square feet (0.743m ²) of cockpit sole will meet this requirement.			
	2.1.5.2	A boat's maximum cockpit volume for cockpits not open to the sea, including any compartments capable of flooding, to lowest points of coaming over which water can adequately escape, shall not exceed 0.08 x LOA x Max. Beam x Freeboard aft. The cockpit sole shall be at least 0.02 x LOA above LWL.			
Hull and Structure: Through Hulls	2.1.6	A boat's through-hull openings below the waterline shall be equipped with sea cocks or valves, except for integral deck scuppers, speed transducers, depth finder transducers and the like; however a means of closing such openings shall be provided.			
Hull and Structure: Stability	2.2.3	A boat with moveable or variable ballast (water or canting keel) shall comply with the requirements of Appendix K.			
Hull and Structure: Accommodations	2.3.1	A boat shall be equipped with a head or a fitted bucket.			
Hull and Structure: Accommodations	2.3.2	A boat shall have bunks sufficient to accommodate the off watch crew.			
Hull and Structure: Accommodations	2.3.3	A boat shall have a stove with a fuel shutoff.			
Hull and Structure: Accommodations	2.3.5	A boat shall have adequate hand holds below decks.			
Hull and Structure: Lifelines	2.4.1	A boat's deck including the headstay shall be surrounded by a suitably strong enclosure, typically consisting of lifelines and pulpits, meeting the requirements in 2.4.2 to 2.4.7.			
Hull and Structure: Lifelines	2.4.2	A boat's stanchion and pulpit bases shall be within the working deck.			
Hull and Structure: Lifelines	2.4.3	Bow pulpits may be open, but the opening between the vertical portion of stanchion pulpit and any part of the boat shall not exceed 14.2" (360mm).			
Hull and Structure: Lifelines	2.4.4	Lifelines shall be uncoated stainless steel wire. A multipart-lashing segment not to exceed 4" per end termination for the purpose of attaching lifelines to pulpits is allowed. Lifelines shall be taut.			
Hull and Structure: Lifelines	2.4.4.1	Lifeline deflection shall not exceed the following: a) When a deflecting force of 9 lbs (40N) is applied to a lifeline midway between supports of an upper or single lifeline, the lifeline shall not deflect more than 2" (50mm). This measurement shall be taken at the widest span between supports that are aft of the mast. b) When a deflecting force of 9 lbs (40N) is applied midway between supports of an intermediate lifeline of all spans that are aft of the mast, deflection shall not exceed 5" (120mm) from a straight line between the stanchions.			
Hull and Structure: Lifelines	2.4.5	The maximum spacing between lifeline supports (e.g. stanchions and pulpits) shall be 87" (2.2m).			
Hull and Structure: Lifelines	2.4.6	Boats under 30' (9.14m) shall have at least one lifeline with 18" (457mm) minimum height above deck, and a maximum vertical gap of 18" (457mm). Taller heights will require a second lifeline. The minimum diameter shall be 1/8" (3mm).			
Hull and Structure: Lifelines	2.4.7	Boats 30' and over (9.14m) shall have at least two lifelines with 24" (762mm) minimum height above deck, and a maximum vertical gap of 15" (381mm). The minimum diameter will be 5/32" (4mm) for boats to 43' (13.1m) and 3/16" (5mm) for boats over 43' (13.1m).			
Hull and Structure: Lifelines	2.4.8	Toe rails shall be fitted around the foredeck from the base of the mast with a minimum height of 3/4" (18mm) for boats under 30' (9.14m) and 1" (25mm) for boats over 30'. An additional installed lifeline that is 1-2" (25-51mm) above the deck will satisfy this requirement for boats without toerails.			
Hull and Structure: Dewatering pumps	2.5.1	A boat shall have a permanently installed manual bilge pump of at least a 10 GPM (37.8 liter per minute) capacity and which is operable from on deck with the cabin closed with the discharge not dependent on an open hatch. Unless permanently attached to the pump, the bilge pump handle shall be securely attached to the boat in its vicinity via a lanyard or catch. A bilge pump discharge shall not be connected to a cockpit drain. The bilge pump shall not discharge into a cockpit unless that cockpit opens aft to the sea.			
Hull and Structure: Mast and Rigging	2.6	A boat shall have the heel of a keel-stepped mast securely fastened to the mast step or adjoining structure.			
Hull and Structure: Mechanical Propulsion	2.7.1	A boat shall have a mechanical propulsion system that is quickly available and capable of driving the boat at a minimum speed in knots equivalent to the square root of LWL in feet (1.81 times the square root of the waterline in meters) for 10 hours.			
Hull and Structure: Mechanical Propulsion	2.7.3	The boat's engine and generator installation (if so equipped) must conform to ABYC, ISO, or U.S. Coast Guard standards.			
Safety Equipment: Personal	3.1.1	Each crewmember shall have a life jacket that provides at least 33.7lbs (150N) of buoyancy, intended to be worn over the shoulders (no belt pack), meeting either U.S. Coast Guard or ISO specifications. Alternatively, each crewmember shall have an inherently buoyant offshore life jacket that provides at least 22lbs (100N) of buoyancy meeting either U.S. Coast Guard or ISO specifications.			
Safety Equipment: Personal	3.1.2	Life jackets shall be equipped with crotch or leg straps, a whistle, a waterproof light, be fitted with marine-grade retro-reflective material, and be clearly marked with the boat's or wearer's name, and be compatible with the wearer's safety harness. If the life jacket is inflatable, it shall be regularly checked for air retention.			
Safety Equipment: Personal	3.1.4	Each crewmember shall have a safety harness and compatible safety tether not more than 67" (2m) long with a minimum tensile strength of 4500 lb. (20kN). The tether shall have a snap hook at its far end and a means to quickly disconnect the tether at the chest end.			
Safety Equipment: Deck Safety	3.2.1	A boat shall carry jacklines with a breaking strength of at least 4500 lb. (20kN) which allow the crew to reach all points on deck, connected to similarly strong attachment points, in place while racing.			
Safety Equipment: Deck Safety	3.2.2	A boat shall have adequate clipping points or jacklines that allow the crew to clip on before coming on deck and unclip after going below.			
Safety Equipment: Navigation Lights	3.3.1	A boat racing between sunset and sunrise shall carry navigation lights that meet U. S. Coast Guard or applicable government requirements mounted so that they will not be obscured by the sails nor be located below deck level.			
Safety Equipment: Navigation Lights	3.3.2	A boat shall have a second set of navigation lights that comply with US Coast Guard or applicable government requirements and which can be connected to a different power source than the primary lights.			
Safety Equipment: Fire Extinguishers	3.4	A boat shall carry fire extinguisher(s) that meets U.S. Coast Guard or applicable government requirements, when applicable.			
Safety Equipment: Sound Producing Equipment	3.5	A boat shall carry sound-making devices that meets U.S. Coast Guard or applicable government requirements, when applicable.			
Safety Equipment: Visual Distress Signals	3.6.4	A boat shall carry U.S. Coast Guard (or applicable government entity) flares or approved S.O.S Distress light meeting day-night requirements; in either case, not older than the expiration date.			
Safety Equipment: Visual Distress Signals	3.6.5	Boat flares stored inside of life rafts may not be used to satisfy the flare requirement.			
Safety Equipment: Man Overboard	3.7.1	A boat shall carry a Lifesling or equivalent man overboard rescue device equipped with a self igniting light stored on deck and ready for immediate use.			
Safety Equipment: Man Overboard	3.7.2	A boat shall have a man overboard pole and flag, with a lifebuoy, a self-igniting light, a whistle, and a drogue attached. A self-inflating Man Overboard Module, Dan Buoy or similar device will satisfy this requirement. Self-inflating apparatus shall be tested and serviced in accordance with the manufacturer's specifications. These items shall be stored on deck, ready for immediate use, and affixed in a manner that allows for a "quick release".			
Safety Equipment: Man Overboard	3.7.3	A boat shall have a throwing sock-type heaving line of 50' (15m) or greater of floating polypropylene line readily accessible to the cockpit.			
Safety Equipment: Man Overboard	3.7.4	A boat shall carry a Coast Guard or applicable government approved "throwable device". If the device carried under 3.7.1 or 3.7.2 satisfies this requirement, then no additional device is needed.			
Safety Equipment: Emergency Communications	3.8.1	A boat shall have a permanently installed 25-watt VHF radio connected to a masthead antenna by a co-axial feeder cable with no more than a 40% power loss. Such radio shall have DSC capability, have an antenna of at least 15" (381mm) in length, be connected to or have an internal GPS, and have the assigned MMSI number (unique to the boat) programmed into the VHF.			
Safety Equipment: Emergency Communications	3.8.2	A boat shall have a watertight handheld VHF radio or a handheld VHF radio with waterproof cover. This radio shall have DSC/GPS capability with an MMSI number properly registered to the vessel.			
Safety Equipment: Emergency Communications	3.8.4	A boat shall have an emergency VHF antenna with sufficient coax to reach the deck.			
Safety Equipment: Emergency Communications	3.9	All boats shall have an AIS Transponder, sharing a masthead VHF antenna via a low loss AIS antenna splitter. An acceptable alternative is a dedicated AIS antenna that is a minimum of 0.9 meters long, mounted with its base at least 3 meters above the water, and fed with coax that has a maximum 40% power loss.	Recommended - Not required		
Safety Equipment: Emergency Communications	3.14	A boat shall carry a GPS receiver.			
Safety Equipment: Emergency Communications	3.15	A boat shall carry an electronic means to record the position of a man overboard within ten seconds. This may be the same instrument listed in 3.14.			
Safety Equipment: Emergency Communications	3.16.1	A boat shall carry a 406MHz EPIRB that is properly registered to the boat. This device shall be equipped with an internal GPS.			
Safety Equipment: Navigation	3.17	A boat shall have a knotmeter and/or distance-measuring instrument.			
Safety Equipment: Navigation	3.18	A boat shall have a permanently installed depth sounder that can measure to depths of at least 200 ft. (61m).			
Safety Equipment: Navigation	3.19.1	A boat shall have a permanently mounted magnetic compass independent of the boat's electrical system suitable for steering at sea.			
Safety Equipment: Navigation	3.19.2	A boat shall have a second magnetic compass suitable for steering at sea which may be handheld.			
Safety Equipment: Navigation	3.20	A boat shall have non-electronic charts that are appropriate for the race area.			
Safety Equipment: Damage Control	3.22	A boat shall carry soft plugs of an appropriate material, tapered and of the appropriate size, attached or stowed adjacent to every through-hull opening.			
Gear: Anchoring	3.23	A boat shall carry one anchor, meeting the anchor manufacturer's recommendations based on the yacht's size, with a suitable combination of chain and line.			
Gear: Lights	3.24.1	A boat shall carry a watertight, high-powered searchlight, suitable for searching for a person overboard at night or for collision avoidance.			
Gear: Lights	3.24.2	A boat shall carry a watertight flashlight for each crewmember with spare batteries in addition to the above.			
Gear: Medical Kits	3.25	A boat shall carry a first aid kit and first aid manual suitable for the likely conditions of the passage and the number of crew aboard.			
Gear: Radar Reflectors	3.26	A boat shall carry an 11.5" (292mm) diameter or greater octahedral radar reflector or one of equivalent performance.			
	3.27.1	A boat shall carry two sturdy buckets of at least two gallons (8 liters) capacity with lanyards attached.			
Gear: Safety Diagram	3.28	A boat shall post a durable, waterproof diagram or chart locating the principal items of safety equipment and through hulls in the main accommodation area where it can be easily seen.			
Gear: Emergency Steering	3.29.1	A boat shall have an emergency tiller, capable of being fitted to the rudder stock.			
Gear: Spare Parts	3.30	A boat shall carry tools and spare parts, including an effective means to quickly disconnect or sever the standing rigging from the hull.			
Gear: Identification	3.31	All lifesaving equipment shall bear retro-reflective material and be marked with the yacht's or wearer's name. The exception would be for new equipment or rented equipment (e.g. life rafts) that would require the unpacking of sealed equipment in order to meet this requirement. The boat name shall be added during the first servicing of any new equipment.			
Gear: Cockpit Knife	3.32	A boat shall carry a strong, sharp knife, sheathed and securely restrained which is readily accessible from the deck and/or cockpit.			
Sails: Mainsail Reefing	3.33.1	A boat shall have a mainsail reefing capable of reducing the luff length by at least 10%.			
Rigging: Halyards	3.35	A boat shall not be rigged with any halyard that requires a person to go aloft in order to lower a sail.			
Rigging: Boom Support	3.36	A boat over 30' LOA (9.14m) shall have a means to prevent the boom from dropping if support from the mainsail or inboard fails.			
Gear: Life Rafts	3.39	A boat shall carry adequate inflatable life raft(s) designed for saving life at sea with designed capacity for containing the entire crew. The raft shall be SOLAS, ISAF, ISO 9650-1 or ORC approved. The raft shall be stored in such a way that it is capable of being launched within 15 seconds. Boats built after 01/06/2001 shall have the life raft stowed in a deck mounted rigid container or stowed in watertight or self-draining purpose built rigid compartment(s) opening adjacent to the cockpit or the working deck. Boats built prior to 01/06/2001 may alternatively stow the life raft in a valise not weighing over 88 lbs. securely below deck and adjacent to the companionway. The life raft(s) shall hold current certificate(s) of inspection.			
Gear: Life Rafts	3.40	A boat shall have a grab bag with a lanyard and clip for each life raft. The grab bag shall have inherent flotation and be of a bright fluorescent color containing at least an EPIRB, and a watertight handheld VHF radio. The VHF radio and EPIRB need not be in addition to the prior requirements.			
Skills: Emergency Steering	4.1.1	A boat's crew shall be aware of multiple methods of steering the boat with the rudder disabled, and shall have chosen and practiced one method of steering the boat with the rudder disabled and be prepared to demonstrate said method of steering both upwind and downwind.			
Skills: Man Overboard	4.2	Annually, two-thirds of the boat's racing crew shall practice man-overboard procedures on the boat. The practice shall consist of marking and returning to a position on the water, and demonstrating a method of hoisting a crewmember back on deck, or other consistent means of reboarding the crewmember.			
Skills: Safety at Sea Training	4.3.1	At least 30% of those aboard the boat, but not fewer than two members of the crew, unless racing single-handed, including the person in charge, shall have attended a one-day or two-day US Sailing Safety at Sea Seminar within the last 5 years, including online courses when available, or other courses as accepted by US Sailing or other national authority.			
Skills: Crew Training	4.4	As required in 1.2 above the person in charge shall ensure that all crew members know where all emergency equipment is located and how to operate the equipment. In addition, the person in charge and crew should discuss how to handle various emergency situations including Crew Overboard, Grounding, Loss of steering, Flooding, Fire, Dismasting, and Abandon Ship.			

I have prepared and inspected my sailing vessel taking full and complete responsibility for its condition. I acknowledge that my sailing vessel meets the requirements as provided in this US Sailing Safety Equipment Requirements (SER) for entry into the Pacific NW Offshore Yacht Race, and I understand and accept my responsibility for the safety of my boat and crew as referenced in SER 1.2 and as provided in the Racing Rules of Sailing rule 4, Decision to Race. I agree to resolve any issues identified during the demonstration of compliance before the start of the Pacific NW Offshore Yacht Race 2021.

I further understand that this SER inspection is in no way a certification, representation, or guarantee that this sailing vessel meets or exceeds any standard of safety or represents any standard of use, and that this inspection does not imply any acceptance of liability on the part of the Inspectors or CYC of Portland (the Organizing Authority) of the Pacific NW Offshore Yacht Race. I agree to indemnify and hold harmless the Organizing Authority, officers, sponsors, agents, employees and associates from any claims, litigation, or liability arising from any person who makes any claim whatsoever in association with this SER and the corresponding inspection.

Sailing Vessel

Skipper's Name

Signature

Date

Inspector's Name

Signature

Date